



UNIQUE TMC RETROFIT OFFER

**Change to a new TMC compressor now
and get a FREE INSTALLATION KIT
and SERVICE CD**



- **Extremely easy to install**
- **Small footprint**
- **Free installation kit**
- **Free service CD**

All TMC compressors offers many advantages:


- **Compact design – high efficiency**
- **Marine approved components**
- **Engineered to withstand 50°C ambient temperature**
- **Easy-to-use controller, pre-programmed from factory**
- **Simple access to all service points**
- **Clean – producing oil-free air**
- **Low noise level**

TO ORDER OR REQUEST MORE INFORMATION, E-MAIL US AT retrofit@tmc.no




THE NO. 1 MARINE SCREW COMPRESSOR

www.tmc.no

**Capacities and dimensions are subject to change without notice.
Before installation, obtain correct dimensions from technical drawings.**

Type and motor kW	Capacity (nom. press.) [m ³ /h]	Capacity (nom. press.) [m ³ /min]	Capacity (nom. press.) [c.f.m.]	Nominal pressure [bar]	Max. pressure [bar]	Nominal pressure [psi]	Max. pressure [psi]	Weight [kg]	Dimensions [mm]
TMC 6-8	51.0	0.85	30	7	8	101.5	116.0	250	
TMC 6-10	40.2	0.67	24	9	10	130.5	145.0	250	
TMC 9-8	69.0	1.15	41	7	8	101.5	116.0	258	
TMC 9-10	54.6	0.91	32	9	10	130.5	145.0	258	
TMC 14-8	104.4	1.74	61	7	8	101.5	116.0	282	
TMC 14-10	85.8	1.43	50	9	10	130.5	145.0	282	
TMC 18-8	150.0	2.50	88	7	8	101.5	116.0	335	
TMC 18-10	126.0	2.10	74	9	10	130.5	145.0	335	
TMC 21-8	172.8	2.88	102	7	8	101.5	116.0	350	
TMC 21-10	144.6	2.41	85	9	10	130.5	145.0	350	
TMC 26-8	204.0	3.40	120	7	8	101.5	116.0	380	
TMC 26-10	171.0	2.85	101	9	10	130.5	145.0	380	
EMH 21-8	207.16	3.46	122	7	8	101.5	116.0	598	
EMH 21-10	152.4	2.54	90	9	10	130.5	145.0	598	
EMH 21-13	125.4	2.09	74	12	13	174.0	188.5	598	
EMH 26-8	227.4	3.79	134	7	8	101.5	116.0	628	
EMH 26-10	192.0	3.2	113	9	10	130.5	145.0	628	
EMH 26-13	149.4	2.49	88	12	13	174.0	188.5	628	
EMH 35-8	315.6	5.26	186	7	8	101.5	116.0	645	
EMH 35-10	263.4	4.39	155	9	10	130.5	145.0	645	
EMH 35-13	208.8	3.48	123	12	13	174.0	188.5	645	
EMH 44-8	378.0	6.30	222	7	8	101.5	116.0	670	
EMH 44-10	311.4	5.19	183	9	10	130.5	145.0	670	
EMH 44-13	264.0	4.40	155	12	13	174.0	188.5	670	
TMC 54-8	544.8	9.08	321	7	8	101.5	116.0	1230	
TMC 54-10	432.0	7.20	254	9	10	130.5	145.0	1230	
TMC 54-13	357.0	5.95	210	12	13	174.0	188.5	1230	
TMC 65-8	618.0	10.30	364	7	8	101.5	116.0	1250	
TMC 65-10	520.2	8.67	306	9	10	130.5	145.0	1250	
TMC 65-13	434.4	7.24	256	12	13	174.0	188.5	1250	
TMC 85-8	738.0	12.30	434	7	8	101.5	116.0	1350	
TMC 85-10	654.0	10.90	385	9	10	130.5	145.0	1350	
TMC 85-13	544.8	9.08	321	12	13	174.0	188.5	1350	

* On air-cooled only.

TMC Smart Air – frequency controlled compressors									
Type and motor kW	Capacity (nom. press.) [m ³ /h]	Capacity (nom. press.) [m ³ /min]	Capacity (nom. press.) [c.f.m.]	Nominal pressure [bar]	Max. pressure [bar]	Nominal pressure [psig]	Max. pressure [psig]	Weight [kg]	Dimensions [mm]
TMC 20 SA - 7.5	70.8-201	1.18-3.35	42-118	7	7.5	101.5	108.8	524	
TMC 20 SA - 10	70.8-171.0	1.18-2.85	42-101	9	10	130.5	145	524	
TMC 20 SA - 13	70.8-150.0	1.18-2.50	42-88	12	13	174.0	188.5	524	
TMC 40 SA - 7.5	73.8-390	1.23-6.5	43-230	7	7.5	101.5	108.8	685	
TMC 40 SA - 10	71.4-343.8	1.19-5.73	42-202	9	10	130.5	145	685	
TMC 40 SA - 13	71.4-306	1.19-5.1	42-180	12	13	174.0	188.5	685	
TMC 60 SA - 7.5	114-564	1.9-9.4	67.1-331.9	7	7.5	101.5	108.8	1220	
TMC 60 SA - 10	126-492	2.1-8.2	74.2-289.6	9	10	130.5	145	1220	
TMC 60 SA - 13	126-396	2.1-6.6	74-233	12	13	174.0	188.5	1220	
TMC 80 SA - 7.5	114-690	1.9-11.5	67-406.1	7	7.5	101.5	108.8	1330	
TMC 80 SA - 10	114-594	1.9-9.9	67-350	9	10	130.5	145	1330	
TMC 80 SA - 13	114-486	1.9-8.1	67-286	12	13	174.0	188.5	1330	

* On air-cooled only.

